

DATASHEET

Chicago Metallic[™] T24 3810




Sounds Beautiful


Chicago Metallic™ T24 3810

- 24 mm grid with universal mainrunner and joggled-end cross tees
- 38mm main and cross tees for heavy load bearing and compatibility with accessories.
- A strong and stable grid which can be easily demounted
- Used to create concealed and exposed ceiling solutions
- Fire rating A1 as per EN 13501-1
- An audible 'click' for fast and accurate installation

Cross-section



Compatible tiles



Coupling

Joggled end



Assortment

Product group		Component description	Height (mm)	Length (mm)	Body Material thickness	Colour	Pcs per pack	Lm per pack	Kg per pack
Main runner									
T24 MR CLICK		Main runner T24 Click	38	3600	0.4mm	02	20	72	29.3
Cross tee									
T24 CT CLICK		Cross tee T24 Click	38	600	0.27mm	02	60	36	9.8
T24 CT CLICK			38	1200	0.27mm	02	60	72	19.1
Wall angle options									
L24x24		L Wall angle 24 x 24mm	24	3000	0.4mm	02	40	120	19.7
W20x10x10x14		W Profile 20 x 10 x 10 x 14mm	20	3000	0.4mm	02	40	120	20
Accessories									
FH B		Hanger. Height 57.5mm. Max weight 35kg	57.5	21.5			200		3.21



Position of slots and suspension holes

Product group	Component description	Height (mm)	Length (mm)	Slots	Distance between slots (mm)
T24 MR CLICK	Main runner T24 Click	38	3600	24	 75 / 150 / 22 x 150 / 75
T24 CT CLICK	Cross tee T24 Click	38	600	0	 600
T24 CT CLICK		38	1200	1	 600 / 600

Performance



Load bearing capacity

Kg/m ²	
Hanger distance (mm)	Maximum deflection
1200	3.3 mm
	21



Reaction to fire

Non-combustible

Sounds Beautiful

