

DATASHEET

Chicago Metallic Ultraline T15 3500




Sounds Beautiful

Chicago Metallic Ultraline T15 3500

- Grid with an aesthetic shape and central groove creating a designer ceiling finish
- Grid with a bayonet main runner coupling and 'click' cross tee couplings
- 41 mm main and cross tees with range of accessories
- Special accessories can be adapted on the central groove to hang signages
- Fire rating A1 as per EN 13501-1
- An audible 'click' for fast and accurate installation

Cross-section




Compatible tiles

Semi-concealed



Coupling

Butt-cut end






Assortment

Product group		Component description	Height (mm)	Length (mm)	Body Material thickness:	Colour	Pcs per pack	Lm per pack	Kg per pack
Main runner									
UL MR		Ultraline main runner	41	3600	0.38mm	8WB	20	72	22.35
UL MR			41	3600	0.38mm	02	20	72	22.35
UL MR			41	3000	0.38mm	8WB	20	60	18.95
UL MR			41	3000	0.38mm	02	20	60	18.95
Cross tee									
UL CT		Ultraline cross tee	41	600	0.38mm	8WB	70	42	12.9
UL CT			41	600	0.38mm	02	70	42	12.9
UL CT		Ultraline cross tee - w/o miter	41	1200	0.38mm	8WB	40	48	14.8
UL CT			41	1200	0.38mm	02	40	48	14.8
UL CT		Ultraline cross tee - with 1 slot	41	1200	0.38mm	8WB	40	48	14.8
UL CT			41	1200	0.38mm	02	40	48	14.8
Wall angle options									
L20x14		L Wall angle 20 x 14mm	20	3000	0.4mm	02	40	120	14.78
W22x15x15x15		W Profile 22 x 15 x 15 x 15mm	22	3000	0.4mm	02	40	120	28.5
Accessories									
SH 80		Direct suspension clip. T-profile H 80mm. Max. weight 35 kg	54.6	36			150		3.32
FH B		Hanger. Height 57.5mm. Max weight 35kg	57.5	21.5			200		3.21
UL BOLT M6		Bolt M6x25 for Ultraline					100		0.7



Position of slots and suspension holes

Product group	Component description	Height (mm)	Length (mm)	Slots	Distance between slots (mm)
UL CT	Ultraline cross tee	41	600	0	 600
UL CT	Ultraline cross tee - w/o miter	41	1200	1	 600 / 600
UL CT	Ultraline cross tee - with 1 slot	41	1200	1	 600 / 600
UL MR	Ultraline main runner	41	3600	6	 300 / 600 / 4 x 600 / 300
UL MR		41	3000	5	 300 / 600 / 3 x 600 / 300

Performance



Load bearing capacity

Hanger distance (mm)	Kg/m ²
	Maximum deflection
	3.3 mm
1200	12



Reaction to fire

Non-combustible

Sounds Beautiful

